# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 Date of issue: 07/15/2021 Revision date: 07/15/2021 Version: 1.2

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

: SUPER SLICK SLICK STUFF (Aerosol) Product name

Product code : NAICS 325998

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant

Details of the supplier of the safety data sheet

Protexall Products, Inc. 73356 Highway 41 Pearl River, LA 70452 - USA T (386) 668-5225

**Emergency telephone number** 

Emergency number : 1-800-458-2699

### **SECTION 2: Hazards identification**

### Classification of the substance or mixture

#### **GHS-US** classification

Flammable Aerosol 1 Gases under pressure - liquefied gas Skin irritation 2 Skin sensitization 1 Aspiration toxicity 1

#### **Label elements** 2.2.

### **GHS-US** labelling

Hazard pictograms (GHS-US)



GHS04





Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

: Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Other hazards

No additional information available

### **SECTION 3: Composition/information on ingredients**

# **Substance**

Not applicable

#### **Mixture** 3.2.

Product identifier	%	GHS-US classification
Trade Secret	10 - 30	Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1
	Trade Secret	

04/23/2020 EN (English) Page 1

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Name	Product identifier	%	GHS-US classification
Trade Secret solvent 2	Trade Secret	30 - 60	Flam. Liq. 3 Asp. Tox. 1
Petroleum gases, liquefied, sweetened	(CAS No) 68476-86-8	15 - 40	Flam. Gas 1 Liquefied gas
Trade Secret base oil 1	Trade Secret	5 - 15	Asp. Tox. 1
Trade Secret base oil 2	Trade Secret	5 - 15	Asp. Tox. 1
Trade Secret base oil 3	Trade Secret	< 5	Acute Tox. 4 (Oral)

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation

: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn.

If irritation persists, get medical attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

Symptoms/injuries after skin contact

: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause an allergic skin reaction.

Symptoms/injuries after eye contact

: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Powder, water fog, foam, carbon dioxide.

Unsuitable extinguishing media : Straight streams of water.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.

Explosion hazard

: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.3. Advice for firefighters

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

### 6.2. Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Scoop up material and place in a disposal container. Provide ventilation.

# 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

07/15/2021 EN (English) 2/6

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

# **SECTION 7: Handling and storage**

### Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

### Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

### **Control parameters**

Trade Secret solvent 1		
ACGIH	Not applicable	
OSHA	Not applicable	

Trade Secret solvent 2		
ACGIH	Not applicable	
OSHA	Not applicable	

Petroleum gases, liquefied, sweetened (68476-86-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
ACGIH	ACGIH STEL (ppm)	1000 ppm	
OSHA	Not applicable		

Trade Secret base oil 1		
ACGIH	Not applicable	
OSHA	Not applicable	

Trade Secret base oil 2		
	ACGIH	Not applicable
	OSHA	Not applicable

Trade Secret base oil 3		
ACGIH	Not applicable	
OSHA	Not applicable	

# **Exposure controls**

Hand protection

Eye protection

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

Wear chemically resistant protective gloves.

recommended exposure limits.

Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

07/15/2021 EN (English) 3/6

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas/Pressurized Liquid

Appearance : Aerosol

Colour No data available Odour No data available Odour threshold No data available рΗ No data available Relative evaporation rate (butylacetate=1) : No data available No data available Melting point Freezing point : No data available **Boiling point** No data available Flash point : No data available : No data available Auto-ignition temperature Decomposition temperature No data available Flammability (solid, gas) No data available Vapour pressure No data available Relative vapour density at 20 °C : No data available 0.7609 g/cm<sup>3</sup> Relative density Solubility No data available

Viscosity, kinematic : 1.038 cSt @ 40 °C (68 °F)

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

### 9.2. Other information

Partition coefficient: n-octanol/water

Additional information : Heat of Combustion: 42.78 kJ/g

Flame Projection Ignition: 90 cm

No data available

No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Log Kow

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

# 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

SUPER SLICK STUFF (Aerosol)		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	No data available	

07/15/2021 EN (English) 4/6

Persistence and degradability

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

cording to the Hazard Communication Standard (CFR29	0 1910.1200) HazCom 2012
SUPER SLICK SLICK STUFF (Aerosol)	
LC50 inhalation rat	> 5 mg/l/4h
Trade Secret solvent 1	
LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5 g/kg
Trade Secret solvent 2	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Petroleum gases, liquefied, sweetened (6847 LC50 inhalation rat	658 mg/l/4h
LC30 ITITIAIAIIOIT TAI	036 HIG/I/4H
Trade Secret base oil 1	
LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	> 5.53 mg/l/4h
Trade Secret base oil 2	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	3900 mg/m <sup>3</sup> /4h
Trade Secret base oil 3	
LD50 oral rat	1750 mg/kg
LD50 dermal rabbit	> 8000 mg/kg
LD50 inhalation rat	21 mg/l/1h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Trade Secret solvent 1	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking
zympiomornjunes alter skili colliact	of the skin. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	<ul> <li>May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.</li> </ul>
SECTION 12: Ecological information	
2.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Description of the second second	
2.2. Persistence and degradability	
SUPER SLICK SLICK STUFF (Aerosol)	

07/15/2021 EN (English) 5/6

Not established.

# Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.3.	Bioaccumu	lative p	otential
-------	-----------	----------	----------

### SUPER SLICK SLICK STUFF (Aerosol)

Bioaccumulative potential Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container.

: 2.1

### **SECTION 14: Transport information**

In accordance with DOT

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : AEROSOLS, flammable, limited quantities

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT)



### **Additional information**

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

# 15.2. US State regulations

# SUPER SLICK SLICK STUFF (Aerosol)

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

# **SECTION 16: Other information**

Date of issue : 07/15/2021
Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

07/15/2021 EN (English) 6/6